

Minimum requirements for POS terminal installation

1. A dry place protected from accidental contact with liquids, preventing any spillage onto or inside the POS terminal.
2. No high voltage devices, or devices that create a magnetic field and can affect the operation of a POS terminal, are allowed near the place of installation.
3. A POS terminal must be installed at the place where payments for goods and/or services are made or cash transactions are performed.
4. Power supply and stable operation of the telephone line at the installation location (not more than 20% of failed data exchange attempts).
5. Connection of a POS terminal to the telephone/power lines requires:
 - 5.1. installation of a distributing box no further than 1.5 metres from the estimated terminal location;
 - 5.2. authorisation to make outgoing calls to numbers in Riga;
 - 5.3. if your company has an internal telephone system (exchange), the installation location requires an analogue port, a ~220 V socket with grounding no further than 3 metres from the intended location of the terminal.
6. Connection of a POS terminal to Internet/power lines requires:
 - 6.1. constant Internet connection (both static and dynamic IP addresses are possible);
 - 6.2. free access to such ports as 18003; 18004; 18007; 11760; 11709; 7608, and the following IP addresses: 195.160.171.96, 193.29.39.1;
 - 6.3. Ethernet cable of sufficient length (a standard computer cable with an RJ45 connector), a ~220 V socket with grounding no further than 3 metres from the estimated terminal location.
7. Installation of a GPRS mobile POS terminal requires a SIM card with the following parameters:
 - 7.1. constant GPRS connection;
 - 7.2. disabled PIN input request;
 - 7.3. good cell coverage area.
8. Installation of a Wi-Fi mobile POS terminal requires a wireless Internet router with a permanent internet connection.